

MEHRASL

MANUFACTURING CORPORATION

Cassette Type fan coil unit



CC 9504

CASSETTE TYPE FAN COIL 4 Ways

MODEL			FC402	FC403	FC404	FC406
Nominal Air Flow			200 CFM	300 CFM	400 CFM	600 CFM
Air Flow	H	m ³ /hr	360	510	680	1020
	M		300	420	560	780
	L		250	350	460	600
Cooling Cap.	H	W	2000	3000	4000	5670
	M		1700	2550	3450	4485
	L		1500	2150	2980	3500
Sensible Cooling Cap.	H	W	1450	1760	2840	3958
	M		1290	1580	2510	3300
	L		1160	1410	2190	2735
Heating Cap.	H	W	3000	4150	6240	8505
	M		2810	3520	5450	7040
	L		2480	3150	4700	5775
Noise Level (@ 1 m)		≤ dB(A)	37	39	41	45
Power Supply			220 ~ 240V / 1PH / 50Hz			
Power Input		W	46	52	70	93
Control Method			Remote or Wall Pad			
Cond. Pipe Size		mm	Ø 20			
Water Connection	In	inch	3/4			
	Out	inch	3/4			
Net Weight		Kg	26	26	28	34
Body Dimensions	Length	mm	570			730
	Width		570			730
	Hight		250			290
Front Panel Dimensions		mm	650*650			850*850

Cooling: 27°Cdb /19.5°Cwb entering air temperature, 7°C entering water and 12°C leaving water temperature.

Heating: 21°Cdb entering air temperature, 60°C entering water and water flow is same to cooling water flow.

CASSETTE TYPE FAN COIL 4 Ways

MODEL			FC408	FC4010	FC4012
Nominal Air Flow			800 CFM	1000 CFM	1200 CFM
Air Flow	H	m ³ /hr	1360	1700	2040
	M		1050	1310	1570
	L		800	1010	1210
Cooling Cap.	H	W	7200	9450	10800
	M		6000	7410	8584
	L		5450	5900	6743
Sensible Cooling Cap.	H	W	5450	6520	7260
	M		4186	5490	6190
	L		3832	4630	5210
Heating Cap.	H	W	10800	14000	16470
	M		9350	12050	13740
	L		7690	10000	11400
Noise Level (@ 1 m)		≤ dB(A)	47	47	50
Power Supply			220 ~ 240V / 1PH / 50Hz		
Power Input		W	130	150	231
Control Method			Remote or Wall Pad		
Cond. Pipe Size		mm	Ø 20		
Water Connection	In	inch	3/4		
	Out	inch	3/4		
Net Weight		Kg	36	50	50
Body Dimensions	Length	mm	730	930	
	Width		730	930	
	Hight		290	290	
Front Panel Dimensions		mm	850*850	1050*1050	

Cooling: 27°Cdb /19.5°Cwb entering air temperature, 7°C entering water and 12°C leaving water temperature.

Heating: 21°Cdb entering air temperature, 60°C entering water and water flow is same to cooling water flow.

این قسمت را با بارکدخوان موبایل اسکن کنید!



Email: headoffice@mehrasl.com <http://www.mehrasl.ir>

HEAD OFFICE: No. 17 - ZOHREH St. - MOFATTEH Ave.

TEHRAN 15-888-36981 IRAN

FAX: (0098-21) 88304147

CENTRAL SHOWROOM: No. 92, MOFATEH Ave.

TEHRAN 15-818-65755 IRAN

MANUFACTURING CORPORATION: SALIMI Industrial Zone -

TABRIZ - IRAN

FAX: (0098-41) 34328955

 TEL: (0098-21) 88300801

دفتر فروش مرکزی: تهران ۱۵-۸۸۸-۳۶۸۱ خیابان مفتاح شمالی

خیابان زهره - شماره ۱۷

فاکس: ۰۲۱-۸۸۳۰۴۱۴۷

کارخانجات تولیدی: تبریز - شهرک صنعتی شهید سلیمی

فاکس: ۰۴۱-۳۴۳۲۸۹۵۵

نمایشگاه و فروشگاه مرکزی: تهران ۱۵-۸۱۸-۶۵۷۵۵

خیابان مفتاح جنوبی - شماره ۹۲



۰۲۱- ۸۳۶۴